



US 20170162766A1

(19) **United States**

(12) **Patent Application Publication**
SATO

(10) **Pub. No.: US 2017/0162766 A1**

(43) **Pub. Date: Jun. 8, 2017**

(54) **METHOD FOR PRODUCING LIGHT
EMITTING DEVICE**

Publication Classification

(71) Applicant: **NICHIA CORPORATION**, Anan-shi
(JP)

(72) Inventor: **Yoshiki SATO**, Anan-shi (JP)

(73) Assignee: **NICHIA CORPORATION**, Anan-shi
(JP)

(21) Appl. No.: **15/439,948**

(22) Filed: **Feb. 23, 2017**

Related U.S. Application Data

(63) Continuation of application No. 15/169,747, filed on
Jun. 1, 2016, now Pat. No. 9,614,135.

(30) **Foreign Application Priority Data**

Jun. 1, 2015 (JP) 2015-111781

(51) **Int. Cl.**

H01L 33/56 (2006.01)

H01L 33/50 (2006.01)

H01L 33/54 (2006.01)

H01L 33/44 (2006.01)

(52) **U.S. Cl.**

CPC **H01L 33/56** (2013.01); **H01L 33/44**

(2013.01); **H01L 33/507** (2013.01); **H01L**

33/54 (2013.01); **H01L 2933/005** (2013.01);

H01L 2933/0041 (2013.01)

(57)

ABSTRACT

A method for producing a light emitting device includes spraying a resin mixture onto a light emitting element using a pulse spraying method to deposit the resin mixture on the light emitting element. The resin mixture includes a thixotropy imparting agent. The resin mixture is cured to form a light transmissive member via which light emitted from the light emitting element is to transmit to an outside of the light emitting device.

